

Specifications Table for FTXM-A

				FTXM20A5V1B	FTXM20A2V1B	FTXM25A2V1B	FTXM25A5V1B	FTXM35A5V1B	FTXM35A2V1B	FTXM42A2V1B	FTXM42A5V1B	FTXM50A5V1B	FTXM50A2V1B	FTXM60A2V1B	FTXM71A2V1B		
Power input	Cooling		Nom.	kW	0.019	0.019	0.019	0.019	0.029	0.029	0.031	0.031	0.034	0.034	0.035	0.037	
	Heating		Nom.	kW	0.018	0.018	0.018	0.018	0.019	0.019	0.035	0.035	0.036	0.036	0.034	0.041	
Casing	Colour			White	White	White	White	White	White	White	White	White	White	White	White	White	
Dimensions	Unit		Height	mm	298	298	298	298	298	298	298	298	298	298	298	298	
			Width	mm	804	804	804	804	804	804	804	804	804	804	997	997	
			Depth	mm	252	252	252	252	252	252	252	252	252	252	292	292	
Weight	Unit			kg	11.5	11.5	11.5	11.5	11.5	11.5	11.5	11.5	11.5	14.5	14.5		
Fan	Air flow rate	Cooling	High	m³/min	11.9	11.9	11.9	11.9	13.2	13.2	13.3	13.3	12.7	12.7	15.6	15.8	
			Medium	m³/min	8.9	8.9	8.9	8.9	9.4	9.4	9.8	9.8	10.4	10.4	13.4	13.6	
			Low	m³/min	6.3	6.3	6.3	6.3	7.1	7.1	7.2	7.2	7.8	7.8	11.2	11.4	
			Heating	Silent operation	m³/min	4.9	4.9	4.9	4.9	4.6	4.6	5.0	5.0	5.9	5.9	8.6	9.3
				High	m³/min	11.4	11.4	11.4	11.4	11.1	11.1	14.0	14.0	14.5	14.5	15.9	17.3
				Medium	m³/min	9.2	9.2	9.2	9.2	9.4	9.4	10.0	10.0	11.5	11.5	14.6	15.3
		Low	m³/min	6.9	6.9	6.9	6.9	6.9	6.9	7.1	7.1	8.6	8.6	11.8	12.3		
			Silent operation	m³/min	4.9	4.9	4.9	4.9	5.1	5.1	5.3	5.3	6.9	6.9	10.5	11.2	
Sound power level	Cooling			dBA	54	54	54	54	58	58	60	60	60	60	60	60	
	Heating			dBA	53	53	53	53	53	53	60	60	60	60	59	61	
Sound pressure level	Cooling	High	dBA	41	41	41	41	45	45	45	45	46	46	46	47		
			Medium	dBA	33	33	33	33	37	37	38	38	40	40	42	43	
			Low	dBA	25	25	25	25	29	29	30	30	33	33	37	38	
			Heating	Silent operation	dBA	19	19	19	19	19	19	21	21	27	27	30	32
				High	dBA	39	39	39	39	39	39	45	45	46	46	45	46
				Medium	dBA	34	34	34	34	35	35	37	37	41	41	41	42
		Low	dBA	26	26	27	27	28	28	29	29	34	34	36	37		
			Silent operation	dBA	20	20	20	20	20	20	21	21	31	31	33	34	
Refrigerant	GWP			675	675	675	675	675	675	675	675	675	675	675	675	675	
Piping connections	Liquid	OD	mm	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4		
				Gas	OD	mm	9.5	9.5	9.5	9.5	9.5	9.5	9.5	12.7	12.7	12.7	15.9
	Drain			16	16	16	16	16	16	16	16	16	16	16	16	16	
Control systems	Infrared remote control			ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	ARC466A86	
	Wired remote control			BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	BRC073A1	
Standard Accessories	Installation manual			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Wireless remote control			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Installation plate			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Screw cover			2	2	2	2	2	2	2	2	2	2				
	AAA dry-cell batteries			2	2	2	2	2	2	2	2	2	2	2	2	2	
	Operation manual			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Titanium apatite deodorizing filter			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Silver particle filter			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Remote control holder			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Screw bag			1	1	1	1	1	1	1	1	1	1	1	1	1	
	Power supply	Name			V1	V1	V1	V1	V1	V1	V1	V1	V1	V1	V1	V1	
Phase			1~	1~	1~	1~	1~	1~	1~	1~	1~	1~	1~	1~			
Power supply		Power supply	Frequency	50	50	50	50	50	50	50	50	50	50	50	50	50	
	Voltage		220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240		
Standard Accessories	FTXM60A2V1B													1			
Notes														(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m	(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m		
														(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m; level difference: 0m	(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m; level difference: 0m		
Standard Accessories	FTXM71A2V1B														1		