

# Specifications Table for FTXTM-A / RXTM-A

			FTXTM30A2V1B / RXTM30A2V1B	FTXTM40A2V1B / RXTM40A2V1B	
Cooling capacity	Min.	kW	1.2	1.2	
	Nom.	kW	3	4	
	Max.	kW	4.6	5.2	
Heating capacity	Min.	kW	0.8	0.9	
	Nom.	kW	3.2	4	
	Max.	kW	7.4	8.8	
Nominal efficiency	EER		5.13	4.71	
	COP		5.3	5.51	
	Annual energy consumption		kWh	292	425
	Energy labeling Directive	Cooling		A	A
		Heating		A	A
Space cooling	Energy efficiency class			A+++	A+++
	Capacity	Pdesign	kW	3	4
	SEER			8.65	8.95
	Annual energy consumption		kWh/a	121	156
Space heating (Average climate)	Energy efficiency class			A+++	A+++
	Capacity	Pdesign	kW	3	3.8
	SCOP/A			5.35	5.5
	Pdh Heating capacity at -10°		kW	3	3.8
	Annual energy consumption		kWh/a	785	967
Notes	(1) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.			(1) - Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.	
	(2) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m.			(2) - Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m.	
	(3) - See separate drawing for operation range			(3) - See separate drawing for operation range	
	(4) - See separate drawing for electrical data			(4) - See separate drawing for electrical data	